

VIV-K10 Easy Keypad

The VIV-K10 Easy Keypad is a standalone access control device designed for single-entry points, featuring an integrated keypad and card reader. It supports up to 1000 users (990 normal users and 10 visitor users) and offers three access modes: Card, PIN, or Card + PIN. The device is compatible with 125KHz EM cards and allows for 4 to 6-digit PIN codes. Housed in a robust zinc-alloy enclosure with a powder-coated finish, the VIV-K10 is suitable for outdoor installations, boasting an IP66 waterproof rating. It operates effectively in temperatures ranging from -40°C to 60°C (-40°F to 140°F) and humidity levels between 10% to 90% RH. The device operates on a voltage range of 12 to 18V DC, with idle and active current consumptions of 50mA and 80mA, respectively. Its compact dimensions are 13.6 cm (L) x 5.6 cm (W) x 2.5 cm (H), and it weighs 490g.

Features

- Metal case, backlit keypad
- Waterproof, conforms to IP66
- One relay, 1000 users (990 Normal Users + 10 Visitor Users)
- 3 access modes: Card, PIN, Card + PIN
- Card type: 125KHz EM card
- PIN length: 4~6 digits
- Anti-tamper alarm
- With Doorbell for visitors
- Remote Control for optional



Specifications

Model	VIV-K10
Operating Voltage	12-18 V DC,
Idle Current	50mA
User Capacity	1000 EM card
Frequency	125kHz
Read Distance	2-6 cm
Operating Temperature	-40 °C to +60 °C
Operating Humidity	10% RH – 98% RH
Index of Protection	Waterproof, conforms to IP66
Dimensions	136x56x25 mm
Unit Weight	490 g
Shipping Weight	550 g

Product Size

