

VIV-K6 Easy Keypad Access

The device is a single entry standalone keypad access control. It is an easy to install and operate device, designs in as less as 6 wires for mounting. With user-friendly programming. The compact design makes it good choice for door access. The device is housed in a strong zinc alloy electroplated case. It supports up to 1000 PIN users.

Features

- Fully waterproof and dustproof, meeting IP66 standards for rugged environments.
- Durable, tamper-proof casing to withstand impact and damage.
- Provides clear, color-coded status indicators for easy monitoring.
- Customizable relay output for various external system functions.
- Supports up to 1000 users, including 990 normal and 10 visitor profiles.
- Energy-efficient with only 50mA current draw.
- Alerts if tampering or unauthorized access is detected.
- Keeps door or gate open for extended access when needed.
- Compatible with power sources ranging from 9V to 18V DC.



Specifications

<i>User capacity</i>	<i>User Capacity</i>	<i>1000</i>
	<i>Normal Users</i>	<i>990</i>
	<i>Visitor Users</i>	<i>10</i>
<i>Operating Voltage</i>	<i>Operating Voltage</i>	<i>9-18V DC</i>
	<i>Idle Current</i>	<i>50mA</i>
	<i>Active Current</i>	<i>80mA</i>
<i>Wiring Connection</i>		<i>Relay Output, Exit Button</i>
<i>Relay</i>	<i>Relay</i>	<i>One(NO, NC, Common)</i>
	<i>Adjustable Relay Output Time</i>	<i>0-99 Seconds (5 seconds Default)</i>
	<i>Lock Output Load</i>	<i>3 Amp Maximum</i>
<i>Environment</i>	<i>Environment</i>	<i>Meets IP66</i>
	<i>Operating Temperature</i>	<i>-40°C~60°C(-40°F~140°F)</i>
	<i>Operating Humidity</i>	<i>10%-90% Non-condensing</i>
<i>Physical</i>	<i>Physical</i>	<i>Zinc-Alloy Enclosure</i>
	<i>Surface Finish</i>	<i>Power Coat</i>
	<i>Dimensions</i>	<i>L120 x W49 x H29(mm)</i>
	<i>Unit Weight</i>	<i>295g</i>

Product Size

