

Mini 10/100/1000Base-TX to 1000Base-FX Media Converter

Key Features

- 10/100/1000Base-TX UTP to 1000Base-FX fiber media conversion
- Support IEEE802.3 10Base-T, IEEE802.3u 100Base-TX/FX standards
- Choice of SC, BiDi or other connectors for multimode and singlemode
- Compact package size

The mini 10/100/1000Base-TX to 1000Base-FX Media Converter is fully compliant with IEEE802.3 10Base-T, IEEE802.3u 1000Base-TX/FX protocols.

Technical Specifications:

Data Rates:

- 10/100/1000 Mbps (802.3 10Base-T/802.3u 100Base-T)
- 1000Mbps (100Base-FX)

Input Power Requirements:

- Input voltage DC 5-12V
.....or AC 6-12V 50/60Hz (optional)
- Power consume 3 Watts maximum

Environmental Conditions:

- Operating temperature 0°C to 40°C
- Cooling free air convection
- Storage temperature -20°C to +85°C
- Operating Humidity 90% max, non-condensing

Mechanical Specifications:

- Case Material.....Iron
- Case Color.....Black
- Net Weight.....30g approx. / unit
- Dimensions.....8.5 x4 x 2.3 (cm)

Do not include transceiver length

Warranty : 1year hardware warranty

*Specifications subject to change without notice.

Ordering Information:

Mini1000M-XXXX

*XXXX: supports optic connector / fiber type and distance. For more details, please refer to the list below or contact us.

X X XX

