

## ***VIV-E1 Embedded RFID Access***

*The VIV-E1 is a compact, standalone RFID access control system housed in a durable mini metal case. With its embedded design, it fits seamlessly into various environments and is especially ideal for installation on narrow door frames. Its sturdy construction ensures reliability and protection, making it suitable for both indoor and outdoor use in residential, commercial, or office settings.*

### ***Features***

- *Compact embedded design with mini size for flexible installation*
- *Durable metal case, waterproof and dustproof, compliant with IP66 standard*
- *Supports up to 3000 users with RFID card access*
- *Compatible with 125KHz EM cards for reliable identification*
- *One programmable relay for customizable access control*
- *Latch mode available to keep door or gate open when needed*
- *Tri-colour LED indicator provides clear status display at a glance*



## Specifications

<i>User Capacity</i>		
<i>Operating Voltage</i>	<i>Operating Voltage</i>	<i>9~18 V DC</i>
	<i>Idle Current</i>	<i>≤25mA</i>
	<i>Active Current</i>	<i>≤100mA</i>
<i>Proximity Card Reader</i>	<i>Proximity Card Reader</i>	<i>EM</i>
	<i>Radio Technology</i>	<i>125KHz Proximity Card</i>
	<i>Read Range</i>	<i>0~2cm</i>
<i>Wiring Connections</i>		
<i>Relay</i>	<i>Relay output, exit button</i>	
	<i>Relay</i>	<i>One (NO, NC, Common)</i>
	<i>Adjustable Relay Output Time</i>	<i>0-99 Seconds (5 seconds default)</i>
	<i>Lock Output Load</i>	<i>2 Amp Maximum</i>
<i>Environment</i>	<i>Environment</i>	<i>Meets IP66</i>
	<i>Operating Temperature</i>	<i>-40°C ~ 60°C (-40°F ~ 140°F)</i>
	<i>Operating Humidity</i>	<i>20% RH ~ 98% RH</i>
<i>Physical</i>	<i>Physical</i>	<i>Stainless Steel Plate</i>
	<i>Color</i>	<i>Silver &amp; Black</i>
	<i>Dimensions</i>	<i>115 x 40 x 25 (mm)</i>
	<i>Unit Weight</i>	<i>105g</i>

## Product Size

