

VIV-XK3-D-MF Outdoor Dual-Relay Digital Keypad Access

The VIV-XK3-D-MF is a durable dual-entry access control device featuring an integrated keypad and card reader. It supports up to 999 users with flexible access modes, including Card, PIN, or Card + PIN. Built for security and longevity, it has an all-metal keypad and a hidden key frame for a sleek, tamper-resistant design, making it ideal for residential, commercial, or industrial use.

Features

- Waterproof, conforms to IP66
- Metal case, anti-vandal
- Two relays, 999 users
- PIN length: 1~8 digits
- Multi-color LED status display
- Integrated alarm & buzzer output, can set the volume sound from level 0~5
- Pulse mode, Toggle mode
- Built in light dependent resistor (LDR) for anti tamper
- Backlit keypad, can set always ON, always OFF, or turn off automatically after 60 seconds
- Relay 2 supports external door bell
- Low temperature resistance(-40°C)
- Card type: XK3-D EM: 125KHz EM card / tag
XK3-D MF: Read 13.56MHz NXP Mifare, Mifare Plus, DesFire, Mifare Pro, Mifare UltraLight, Mifare Class 4K, NFC and CPU cards (4 bytes, 7 bytes ISO14443 Type A)





Specifications

<i>User Capacity</i>	999	
<i>Operating Voltage</i>	<i>Operating Voltage</i>	12~28V AC/DC
	<i>Idle Current</i>	<50mA
<i>Radio Technology</i>	<i>Radio Technology</i>	125KHz / 13,56MHz
	<i>Radio Range</i>	2~6cm
<i>Proximity Card Reader</i>	EM or NXP Mifare, Midare Plus, DesFire, Mifare Pro, Mifare UltraLight, Mifare class 4K, NFC And CPU Cards (4 bytes, 7 bytes ISO14443 TypeA)	
<i>PIN Length</i>	1~8 digits	
<i>Wiring Connections</i>	<i>Relay Output , Exit button, Alarm, Door Contact, Doorbell</i>	
	<i>Relay</i>	<i>Tow(NO, NC, Common)</i>
<i>Relay</i>	<i>Adjustable Relay Output Time</i>	0~300 Seconds (5 seconds default)
	<i>Lock Output Load</i>	2 Amp Maximum
	<i>Environment</i>	Meets IP66
<i>Environment</i>	<i>Operating Temperature</i>	-40C ~ 60°C(-40°F ~ 140°F)
	<i>Operating Humidity</i>	0%RH~98%Rh
	<i>physical</i>	Zinc-Alloy
<i>physical</i>	<i>Color</i>	Silver
	<i>Dimensions</i>	L114.5 x W75 X D22 mm
	<i>Unit Weight</i>	360g

Product Size

