

## FO passive components

### Optowire OM3 SC/UPC-LC/UPC Patch cord 2.0mm LSZH Duplex

- Bend Insensitive Fiber & 7.5mm Min. Bend Radius
- Precision Zirconia Ferrule Connectors Ensure Low Loss
- Duplex Zipcord Enhances Mechanical Performance and Reduces Crimping Risk
- LSZH Environmentally Friendly Jacket
- Optical Testing Ensures Network Performance
- Length – Customized



## TECHNICAL SHEET

<b>Connector A</b>	<b>SC/UPC</b>	<b>Connector B</b>	<b>LC/UPC</b>
<b>Fiber Mode</b>	<b>OM3 50/125µm</b>	<b>Fiber Count</b>	<b>Duplex</b>
<b>Fiber Grade</b>	<b>Bend Insensitive</b>	<b>Minimum Bend Radius</b>	<b>7.5mm</b>
<b>Polish Type</b>	<b>UPC</b>	<b>Cable Diameter</b>	<b>2.0 mm</b>
<b>Cable Jacket</b>	<b>LSZH</b>	<b>Return Loss</b>	<b>≥30dB</b>
<b>Wavelength</b>	<b>850nm / 1300nm</b>	<b>Attenuation at 850nm</b>	<b>3.0 dB/km</b>
<b>Insertion Loss</b>	<b>≤0.3 dB</b>	<b>Attenuation at 1300nm</b>	<b>1.0 dB/km</b>
<b>Operating Temperature</b>	<b>-20~70°C</b>	<b>Storage Temperature</b>	<b>-40~80°C</b>