

## VIV-K2 Easy Keypad Access

*VIV-K2 is a single-entry standalone access control device featuring an integrated keypad and RFID card reader. Designed for durability, it is waterproof and ideal for both indoor and outdoor use. The unit supports PIN code and card access, providing flexible entry options without the need for an external controller. Its compact and weather-resistant design makes it a reliable solution for secure entry points in homes, offices, and commercial properties.*

### Features

- One relay, 1000 users (990 Normal Users + 10 Visitor Users)
- 3 access modes: Card, PIN, Card + PIN
- Card type: 125KHz EM card/13.56MHz Mifare card
- Card type: 125KHz EM card/13.56MHz Mifare card
- Operating Temperature: -40°C~60°(-40°F~140°F)
- Anti-tamper alarm





## Specifications

<i>USER Capacity</i>	<i>USER Capacity</i>	<i>1000 Cards/PINS</i>
	<i>Normal Capacity</i>	<i>990</i>
	<i>Visitor Users</i>	<i>10</i>
<i>Operating Voltage</i>	<i>Operating Voltage</i>	<i>12 ~ 18V DC</i>
	<i>Idle Current</i>	<i>50 mA</i>
	<i>Active Current</i>	<i>80 mA</i>
<i>Keypad</i>	<i>12 Keys</i>	
<i>Proximity Card Reader</i>	<i>Proximity Card Reader</i>	<i>EM/mifare Optional</i>
	<i>Radio Technology</i>	<i>125KHz EM Card/13.56MHz Mifare Card</i>
	<i>Read Range</i>	<i>3-6cm</i>
<i>Wiring Connections</i>	<i>Relay Output, Exit Button</i>	
<i>Relay</i>	<i>Relay</i>	<i>ONE(NO, NC, Common)</i>
	<i>Adjustable Relay Output Time</i>	<i>0-99 Seconds (5 Seconds Default)</i>
	<i>Lock Output Load</i>	<i>3 Amp Maximum</i>
<i>Environment</i>	<i>Environment</i>	<i>Indoor</i>
	<i>Operating Temperature</i>	<i>-40°C~60°(-40°F~140°F)</i>
	<i>Operating Humidity</i>	<i>10%RH-90%RH</i>
<i>Physical</i>	<i>Physical</i>	<i>ABS Enclosure</i>
	<i>Color</i>	<i>Black</i>
	<i>Dimensions</i>	<i>12.2L x 5.0 W x 2.1H(cm)</i>
	<i>Unit Weight</i>	<i>150g</i>

## Product Size

